EUROPEAN PATENT OFFICE

*CAPF020073 Re

Patent Abstracts of Japan

CITED BY APPLICANT

US 6445120 correspondos

PUBLICATION NUMBER

2000133150

PUBLICATION DATE

12-05-00

APPLICATION DATE

28-10-99

APPLICATION NUMBER

11307822

APPLICANT:

LG ELECTRONICS INC;


INVENTOR: TAMURA MASATADA;

INT.CL.

H01J 11/02 H01J 11/00

TITLE

PLASMA DISPLAY PANEL



ABSTRACT:

PROBLEM TO BE SOLVED: To improve the light emitting efficiency and luminance by providing a discharge electrode divided from a bus electrode with a first width and extended with the second width larger than the first width and formed with a tip having a small width and an opposite discharge electrode, and depositing a dielectric layer for coating these discharge electrodes on the discharge electrodes while restricting the thickness thereof.

SQLUTION: A first and a second bus electrodes 1300, 1300' are respectively formed of a metal thin film formed of three layers. A first and a second discharge electrodes 1200, 1200' are conductive transparent electrodes such as ITO, and respectively provided with each part of a first and a second branch parts 1210, 1210' divided from the first and the second bus electrodes 1300, 1300' and having a narrow width and central parts 1220, 1220' having a wide width, and a first and a second tips 1230, 1230' having a narrow width. Thickness of a dielectric layer for coating the first and the second discharge electrodes 1200, 1200' for deposition is set at 30-40 µm at parts provided with the first and the second discharge electrodes 1200, 1200' opposite to each other, and set at a value smaller by 10-20 µm than the described thickness at parts on the first and the second discharge electrodes 1200, 1200'.

COPYRIGHT: (C)2000,JPO